

FL-08



Características

- Banda de rodamiento compacta, diseñada para servicio pesado.
- Buena estabilidad direccional.

Medida	Modelo	Tipo	Lonas	Profundidad de grabado mm	Llanta (permitida)	Diámetro Exterior mm	Capacidad de carga kg	Presión de inflado PSI
5.00-8	FL-08	TT	10	11.0	3.00D-8	476	1415	145
18x7-8	FL-08	TT	16	14.0	4.33R-8	462	2145	145
6.00-9	FL-08	TT	12	13.0	4.00E-9	540	1885	145
21x8-9	FL-08	TT	16	15.0	6.00E-9	535	2755	145
6.50-10	FL-08	TT	14	14.0	5.00F-10	588	1950	112
23x9-10	FL-08	TT	20	16.0	6.50F-10	595	3440	145
7.00-12	FL-08	TT	14	15.0	5.00S-12	672	2755	130
27x10-12	FL-08	TT	16	18.0	8.00G-12	681	3900	116
8.15-15	FL-08	TT	14	18.0	7.0-15	707	3900	145
8.25-15	FL-08	TT	18	23.0	6.5-15	836	4745	145
250-15	FL-08	TT	20	20.0	7.50-15	735	5040	145
300-15	FL-08	TT	22	23.0	8.00-15	840	6695	145